

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 197 355 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
05.03.2003 Bulletin 2003/10

(51) Int Cl.7: B60C 11/03, B60C 11/13
// B60C115/00

(43) Date of publication A2:
17.04.2002 Bulletin 2002/16

(21) Application number: 01308626.9

(22) Date of filing: 09.10.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Himuro, Yasuo,
c/o Bridgestone Corporation
Kodaira City, Tokyo (JP)

(30) Priority: 10.10.2000 JP 2000308846

(74) Representative: Whalley, Kevin
MARKS & CLERK,
57-60 Lincoln's Inn Fields
London WC2A 3LS (GB)


(71) Applicant: BRIDGESTONE CORPORATION
Tokyo 104-0031 (JP)

(54) Pneumatic tires

(57) A pneumatic tire comprises a tread portion (1) having a plurality of slant grooves (7a, 7b), in which each slant groove has a steeply slant groove portion (5a, 5b) and a gently slant groove portion (6a, 6b), and the steeply slant groove portion comprises a pseudo-land part (14) of a given shape, and can improve the drainage performance without sacrificing the other tire performances. Such a tire is in particular characterized in that an opening groove width (W1) located at the end (8) of the steeply slant groove portion (5a, 5b) which is close to a tread end is wider than an opening groove width (W2) located at the end (9) of the steeply slant groove

portion which is close to the tire equatorial plane, and the steeply slant groove portion extending in a longitudinal direction of the slant groove (7a, 7b) comprises a groove edge part (31) forming a boundary to an outer surface (33) of a tread land portion, a main groove bottom part (32) mainly forming a groove bottom of the steeply slant groove portion, and a pseudo-land part (14) located in the groove edge part (31) and adjacent to at least one of both side edges (32a, 32b) of the main groove bottom part (32), and the pseudo-land part (14) has such a slant surface (13) that a height thereof is gradually decreased from the groove edge part (31) toward the main groove bottom part (32).

FIG. 1





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 30 8626

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	WO 00 51831 A (HIMURO YASUO ;BRIDGESTONE CORP (JP)) 8 September 2000 (2000-09-08) * figures 1,2A *	1-9	B60C11/03 B60C11/13 //B60C115/00
X	PATENT ABSTRACTS OF JAPAN vol. 1998, no. 05, 30 April 1998 (1998-04-30) -& JP 10 016515 A (BRIDGESTONE CORP), 20 January 1998 (1998-01-20) * abstract * * figures 1-3 *	1-9	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			B60C
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 14 January 2003	Examiner Bibollet-Ruche, D
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background G : non-written disclosure F : intermediate document		1 : theory or principle underlying the invention 2 : earlier patent document, but published only after the filing date D : document cited in the application 3 : document cited for other reasons 4 : document cited for other reasons 5 : member of the same patent family, corresponding document	

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 8626

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

14-01-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0051831	A	08-09-2000	JP 2000247111 A	12-09-2000
			EP 1075971 A1	14-02-2001
			WO 0051831 A1	08-09-2000
JP 10016515	A	20-01-1998	NONE	

EP 01 30 8626

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)



(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
17.04.2002 Bulletin 2002/16

(51) Int Cl.⁷: **B60C 11/03**, B60C 11/13
// B60C115/00

(21) Application number: 01308626.9

(22) Date of filing: 09.10.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
 Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Himuro, Yasuo,**
c/o Bridgestone Corporation
Kodaira City, Tokyo (JP)

(74) Representative: **Whalley, Kevin**
MARKS & CLERK,
57-60 Lincoln's Inn Fields
London WC2A 3LS (GB)

(30) Priority: 10.10.2000 JP 2000308846


(71) Applicant: **BRIDGESTONE CORPORATION**
Tokyo 104-0031 (JP)

(54) **Pneumatic tires**

(57) A pneumatic tire comprises a tread portion (1) having a plurality of slant grooves (7a, 7b), in which each slant groove has a steeply slant groove portion (5a, 5b) and a gently slant groove portion (6a, 6b), and the steeply slant groove portion comprises a pseudo-land part (14) of a given shape, and can improve the drainage performance without sacrificing the other tire performances. Such a tire is in particular characterized in that an opening groove width (W1) located at the end (8) of the steeply slant groove portion (5a, 5b) which is close to a tread end is wider than an opening groove width (W2) located at the end (9) of the steeply slant groove

portion which is close to the tire equatorial plane, and the steeply slant groove portion extending in a longitudinal direction of the slant groove (7a,7b) comprises a groove edge part (31) forming a boundary to an outer surface (33) of a tread land portion, a main groove bottom part (32) mainly forming a groove bottom of the steeply slant groove portion, and a pseudo-land part (14) located in the groove edge part (31) and adjacent to at least one of both side edges (32a,32b) of the main groove bottom part (32), and the pseudo-land part (14) has such a slant surface (13) that a height thereof is gradually decreased from the groove edge part (31) toward the main groove bottom part (32).

FIG. 1



Description

[0001] This invention relates to a pneumatic tire improving a drainage performance without sacrificing the other tire performances such as a steering stability and the like, and more particularly to a so-called high-performance tire having a small aspect ratio and a wide tread width.

[0002] In the conventional pneumatic tire, for example, the tire for use in a passenger car, as shown in FIG. 5, it is general to have a tread pattern defined by arranging circumferential grooves 101-103 extending in parallel to an equatorial plane of the tire, and a plurality of slant grooves 104-106 opening to the circumferential groove 101, 102, extending from the circumferential groove 101, 102 toward each end of the tread, and obliquely extending to the equatorial plane of the tire.

[0003] In such a tread pattern, an excellent drainage performance can be given to the tire by mainly performing the drainage toward the longitudinal direction of the tire through the circumferential grooves and performing the drainage toward the lateral direction of the tire through the slant grooves.

[0004] In the tire having such a tread pattern, as means for further improving the drainage performance, it is useful to make larger a ratio of groove area or so-called negative ratio by enlarging the groove width and the like, or to arrange the slant grooves at a small angle with respect to the circumferential direction of the tire or form so-called high-angle grooves.

[0005] However, the increase of the negative ratio becomes lacking in the rigidity of the land in the tread portion, and also when the slant grooves are arranged as the high-angle groove, a corner part of the land defined by the slant grooves becomes acute and hence the rigidity of each land is lacking. In any case, the sufficient steering stability can not be obtained.

[0006] Moreover, as a construction of the tread pattern for balancedly satisfying both the drainage performance and the steering stability, it is useful to combine the circumferential grooves with the slant grooves as a basic construction and also to change the extending shape of the slant groove between a central region and a side region of the tread portion. Concretely, a portion of the slant groove located in the central region is formed as a steeply slant groove portion inclined at a small angle with respect to the circumferential direction of the tire and a portion of the slant groove located in the side region is formed as a gently slant groove portion inclined at a large angle with respect to the circumferential direction of the tire.

[0007] With respect to the tire having such a tread pattern that the drainage performance and the steering stability are balancedly satisfied, the inventor has made examinations for more improving the drainage performance and confirmed that when water existing in the central region of the tread in the tire contacting with ground is particularly taken into the slant groove and discharged therefrom toward the lateral direction of the tire, the water taken into the slant groove collides with a groove wall of a curved groove portion passing during the movement from the steeply slant groove portion to the gently slant groove portion to thereby easily cause disturbance of the water flow and such a disturbance largely lowers the drainage ability of the slant groove toward the lateral direction of the tire.

[0008] It is, therefore, an object of the invention to provide a pneumatic tire, particularly a high-performance tire improving the drainage performance without sacrificing the other tire performances such as steering stability and the like by adopting a tread pattern provided with slant grooves each comprising a steeply slant groove portion and a gently slant groove portion as a basic construction and arranging a pseudo-land portion at a given position in the steeply slant groove portion of the slant groove.

[0009] According to the invention, there is the provision of in a pneumatic tire comprising a tread portion with a tread pattern defined by a plurality of slant grooves, each of which slant grooves comprising a steeply slant groove portion located in a widthwise central region of the tread portion, (steeply slant groove portion) inclined at a relatively small angle with respect to a circumferential direction of the tire, and (steeply slant groove portion) extending from a top that is one end of steeply slant groove portion which is close to an equatorial plane of the tire toward an end that is the other end of steeply slant groove portion which is close to a tread end, and a gently slant groove portion located in each of both side regions of the tread portion, (gently slant groove portion) inclined at a relatively large angle with respect to the circumferential direction of the tire, and (gently slant groove portion) extending from the end of the steeply slant groove portion or an extension thereof so as to open at the tread end, the improvement wherein an opening groove width (W1) located at the end of the steeply slant groove portion is wider than an opening groove width (W2) located at the top of the steeply slant groove portion, and the steeply slant groove portion extending in a longitudinal direction of the slant groove comprises a groove edge part forming a boundary to an outer surface of a tread land portion, a main groove bottom part mainly forming a groove bottom of the steeply slant groove portion, and a pseudo-land part located in the groove edge part and adjacent to at least one of both side edges of the main groove bottom part, and the pseudo-land part has such a slant surface that a height thereof is gradually decreased from the groove edge part toward the main groove bottom part.

[0010] And also, when it is required to compensate for the rigidity of the land portion while smoothly flowing water from the steeply slant groove portion to the gently slant groove portion, the slant surface of the pseudo-land part is

preferable to have substantially a triangular or trapezoidal and flat or curved surface shape when viewing the tire from a front thereof.

[0011] Furthermore, when it is required to reduce a pattern noise, a pair of adjoining slant grooves located on both sides of a pattern center are preferable to be formed at a phase difference of a half pitch in the circumferential direction of the tire.

[0012] Moreover, when the drainage performance is particularly attached importance, it is preferable to arrange one circumferential main groove extending along the circumferential direction of the tire in a widthwise central position of each half tread zone sandwiched between the pattern center and both the tread ends or in the vicinity of the central position of the half tread zone.

[0013] In addition, when sufficient drainage performance and steering stability are balancedly satisfied, it is preferable to form at least one rib-shaped land portion extending along the circumferential direction of the tire and at least two land rows each comprised of plural blocks in the tread portion.

[0014] In case of mainly aiming at the improvement of the drainage performance, the pseudo-land part is preferable to be arranged adjacent to a side edge of the main groove bottom part located at the pattern-center-side of the main groove bottom part in the steeply slant groove portion. If it is required to compensate for the rigidity of both land portions divided by the steeply slant groove portion, the pseudo-land parts are preferable to be separately arranged adjacent to both side edges of the main groove bottom part in the steeply slant groove portion.

[0015] The invention will be described with reference to the accompanying drawings, wherein:

FIG. 1 is a partly developed view of a tread portion in an embodiment of the pneumatic tire according to the invention;

FIG. 2A is a diagrammatically section view of a pseudo-land portion taken along a line I-I of FIG. 1;

FIG. 2B is a diagrammatically section view of the pseudo-land portion taken along a line II-II of FIG. 1;

FIG. 2C is a diagrammatically section view of the pseudo-land portion taken along a line III-III of FIG. 1;

FIG. 3 is a partly developed view of a tread portion in another embodiment of the pneumatic tire according to the invention;

FIG. 4A is a diagrammatically section view of a pseudo-land portion taken along a line I-I of FIG. 3;

FIG. 4B is a diagrammatically section view of the pseudo-land portion taken along a line II-II of FIG. 3;

FIG. 4C is a diagrammatically section view of the pseudo-land portion taken along a line III-III of FIG. 3;

FIG. 4D is a diagrammatically section view of the pseudo-land portion taken along a line IV-IV of FIG. 3; and

FIG. 5 is a partly developed view of a tread portion in the conventional pneumatic tire.

[0016] In FIG. 1 is partly shown a tread pattern formed on a tread portion in an embodiment of the pneumatic tire according to the invention, in which numeral 1 is a tread portion, numeral 2 a central region, numerals 3a and 3b side regions, numeral 4 a circumferential direction of the tire, numerals 5a and 5b steeply slant groove portions, numerals 6a and 6b gently slant groove portions, and numerals 7a and 7b slant grooves.

[0017] When the tread portion 1 of the tire shown in FIG. 1 is divided into the central region 2 and both side regions 3a, 3b, the tread portion 1 is provided with a plurality of slant grooves 7a, 7b comprising the steeply slant groove portions 5a, 5b located in the central region 2 and extending slantly at a relatively small angle, preferably an angle of no more than 30° with respect to the circumferential direction 4 of the tire, and the gently slant groove portions 6a, 6b located in the side region 3a, 3b and extending slantly at a relatively large angle, preferably an angle of 70-85° with respect to the circumferential direction 4 of the tire.

[0018] In the invention, an extending direction of the steeply slant groove portion 5a, 5b arranged in the central region 2 is constructed so as to substantially coincide with a flowing direction of water in the central region of the tread in the tire contacting with ground to thereby ensure the drainage performance, while the corner portions of the lands defined by the gently slant groove portions 6a, 6b arranged in the side regions 3a, 3b become obtuse to ensure the rigidity of the land, so that a good steering stability can be obtained.

[0019] However, the inventor has examined a possibility of further improving the drainage property with respect to the above tread pattern and obtained the following knowledge.

[0020] That is, it has been confirmed that when water existing in the central region of the tire contacting with ground is taken into the steeply slant groove portions 5a, 5b of the slant grooves 7a, 7b and moved to the gently slant groove portions 6a, 6b to discharge therefrom toward the lateral direction of the tire, if the groove width of the steeply slant groove portion 5a, 5b is made wider, water is easily taken into the steeply slant groove portion 5a, 5b, but the rigidity of the land becomes insufficient, and also water taken into the slant groove 7a, 7b collides with a groove wall of a curved groove portion 29 located between the steeply slant groove portion 5a, 5b and the gently slant groove portion 6a, 6b to easily cause the disturbance in the flowing of water, which largely lowers the drainage ability of the slant grooves 7a, 7b toward the lateral direction of the tire.

[0021] To this end, the inventor has made various studies in order to easily take water existing the central region of the tire contacting with ground into the steeply slant groove portions 5a, 5b without almost lowering the rigidity of the

land and to smoothly move water from the steeply slant groove portions 5a, 5b to the gently slant groove portions 6a, 6b, and found that an opening groove width W1 located at the end 8 of the steeply slant groove portion 5a, 5b in the slant groove 7a, 7b is wider than an opening groove width W2 located at the top 9 of the steeply slant groove portion, and the steeply slant groove portion extending in a longitudinal direction of the slant groove comprises a groove edge part 31 forming a boundary to an outer surface 33 of a tread land portion, a main groove bottom part 32 mainly forming a groove bottom of the steeply slant groove portion, and a pseudo-land part 14 located in the groove edge part 31 and adjacent to at least one of both side edges 32a, 32b of the main groove bottom part 32, and the pseudo-land part 14 has such a slant surface 13 that a height thereof is gradually decreased from the groove edge part 31 toward the main groove bottom part 32. In other words, the pseudo-land part 14 having the slant surface 13 such that the height thereof is gradually decreased from the groove wall 11a toward the groove bottom 12 (more concretely, the main groove bottom part 32) may be formed in the steeply slant groove portion 5a, 5b of the slant groove 7a, 7b and at a position adjacent to at least one groove wall side thereof (the groove wall 11a near to a pattern center 10 in FIG. 1). As a result, the invention has been accomplished.

[0022] FIGS. 2A-2C show section views of the pseudo-land part 14 taken along lines I-I, II-II and III-III of FIG. 1, respectively.

[0023] As seen from the above, according to the invention, by adopting the above construction can be more improved the drainage performance without sacrificing the other tire performances such as steering stability and the like.

[0024] As another embodiment of the invention, the slant surface 13 of the pseudo-land part 14 has substantially a triangular or trapezoidal shape that a zone of the pseudo-land part 14 located at the top 9 of the steeply slant groove portion 5a, 5b, more concretely a zone 16 of the pseudo-land portion 14 located at a side first entering in a ground contact region during the rotation of the tire in an arrow direction 15 as shown in FIG. 1 is tapered. In this case, it is easy to smoothly flow water existing in the central region of the tire contacting with ground from the top 9 of the steeply slant groove portion 5a, 5b into the inside of the steeply slant groove portion 5a, 5b while strengthening the rigidity of a land adjacent to the pseudo-land part 14, particularly a land 18 having an acute zone 17 as shown in FIG. 1.

[0025] Moreover, FIG. 1 shows a case that in order to improve the ground contact property, a slit 30 is arranged between the pseudo-land part 14 and the groove wall 11a of the steeply slant groove portion 5a, 5b. Such a slit 30 can properly be arranged, if necessary.

[0026] And also, the slant surface 13 of the pseudo-land part 14 may have a flat shape or a curved shape.

[0027] Furthermore, when a pair of adjoining slant grooves 7a, 7b located on both sides of the pattern center 10 are arranged at a phase difference L of a half pitch in the circumferential direction 4 of the tire, the timing of the ground contact impact can be shifted between these slant grooves 7a, 7b located on both sides of the pattern center 10, whereby the pattern noise can be reduced.

[0028] Although FIG. 1 shows a case that the pattern center 10 coincides with the position of the equator of the tire, the pattern center 10 may be somewhat shifted from the position of the equator of the tire.

[0029] Moreover, when one circumferential main groove 21a, 21b extending along the circumferential direction 4 of the tire is arranged at a widthwise center position of each of tread half regions 20a, 20b sandwiched between the pattern center 10 and the tread ends 19a, 19b or in the vicinity of the center position of the tread half region, the drainage performance can be more enhanced while ensuring the rigidity of the land located in the central region 2 of the tread.

[0030] Also, it is preferable to form at least one rib-shaped land extending along the circumferential direction 4 of the tire, and at least two land rows each comprising a plurality of blocks and extending along the circumferential direction 4 of the tire on the tread portion 1, whereby the effect capable of simultaneously establishing the sufficient drainage performance and the steering stability is obtained. Moreover, FIG. 1 shows a case that three rows in total of a rib-shaped center land 22 and two medium land rows 23a, 23b located at both sides of the rib-shaped center land 22 are formed between the circumferential main grooves 21a, 21b (rib-shaped land is included in the conception of the land row), and two rows in total of side land rows 24a, 24b are formed respectively between each of the circumferential main groove 21a, 21b and each of the tread ends 19a, 19b. That is, five land rows in total are formed on the tread portion 1.

[0031] In addition, although FIG. 1 shows the case that the pseudo-land part 14 is arranged adjacent to the groove wall 11a located at the pattern-center-10-side of the steeply slant groove portion 5a, 5b, the pseudo-land parts 14a, 14b can be separately arranged adjacent to both groove walls 11a, 11b of the steeply slant groove portion 5a, 5b as shown in FIG. 3, respectively. In the latter case, water can rapidly be taken into the inside of the steeply slant groove portion 5a, 5b.

[0032] When the pseudo-land part 14b is arranged at the groove wall 11b of located at the tread-end-19a, 19b-side of the steeply slant groove portion 5a, 5b, as shown in FIG. 3, it is preferable that the pseudo-land part 14b is formed so as to have substantially a triangular shape or a trapezoidal shape that a zone 25 of the pseudo-land part 14b located at the end-8-side of the steeply slant groove portion 5a, 5b is tapered in view of strengthening the rigidity of a land 27 having an acute zone 26.

[0033] When it is required to more enhance the drainage performance, it is preferable to arrange a width-narrow circumferential sub-groove (not shown) extending along the circumferential direction 4 of the tire between the pattern center 10 and the circumferential main groove 21a, 21b. In case of arranging the circumferential sub-groove, in order to avoid the wandering such as rain groove or the like, it is favorable that when viewing the inside of the circumferential sub-groove toward the extending direction in the developed view of the whole of the tread portion constituting the tire, the sub-groove is constituted so as to have a groove shape that can not see through the whole of the inside of the sub-groove.

[0034] Although the above is described with respect to only a preferred embodiment of the invention, various modifications may be taken within a scope of the invention.

[0035] For example, as shown in FIG. 1, in order to more improve the drainage performance, an auxiliary groove 28 may be arranged between the gently slant groove portions 6a, 6a or 6b, 6b of the slant grooves 7a, 7a or 7b, 7b which are adjacent to each other in the circumferential direction 4 of the tire so as to extend from the groove wall located at the tread-end-side of the steeply slant groove portion in the slant groove and at the final ground contact side during the rotation of the tire in the arrow direction 15 through the circumferential main groove 21a, 21b up to open in the tread end 19a, 19b.

[0036] And also, it is favorable that a curved groove part 29 having a smooth curvature of connecting the steeply slant groove portion 5a, 5b to the gently slant groove portion 6a, 6b is formed in the slant groove 7a, 7b at a position ranging from the circumferential main groove 21a, 21b toward the pattern center 10 in view of the maintenance of the land rigidity, the prevention of the heel and toe wear in the land located in the side region 3a, 3b and the maintenance of the drainage performance toward the lateral direction of the tire.

[0037] Furthermore, the slant surface 13 of the pseudo-land part 14 may be inclined from a position of the height of the groove wall of the steeply slant groove portion 5a, 5b toward the groove bottom 12 as shown in FIGS. 4A-4D, or may be inclined from a position located inward from the above position of the groove wall height in the radial direction of the tire toward the groove bottom 12.

[0038] The following examples are given in illustration of the invention and are not intended as limitations thereof.

Example 1

[0039] A tire of this example is a pneumatic tire having a tread pattern shown in FIG. 1 and a tire size of PSR 205/55R16 (tread width: 170 mm), in which dimensions of circumferential main grooves, slant grooves and the like are shown in Table 1. Moreover, the structure other than the tread portion of the tire is substantially the same as that of the conventional pneumatic tire usually used in a passenger car.

Table 1

	Groove width (mm)	Groove depth (mm)	Groove angle* 1(°)
Circumferential main groove 21a, 21b	7	8	0
Steeply slant groove portion 5a, 5b	10		5 - 25
Gently slant groove portion 6a, 6b	4	6.5	70 - 80
Auxiliary groove 28	2	6.5	70 - 65
Curved part 29	6	8 - 6.5	25 - 70
Pseudo-land part 14	Width of land: 8 - 0 mm, Length of land: 45 - 70 mm, Height of land: 8 - 0 mm		

* 1: Angle with respect to the circumferential direction of tire

Example 2

[0040] A tire of this example is a pneumatic tire having a tread pattern shown in FIG. 3 and a tire size of PSR 205/55R16 (tread width: 170 mm), in which dimensions of circumferential main grooves, slant grooves and the like are shown in Table 2. Moreover, the structure other than the tread portion of the tire is substantially the same as that of the conventional pneumatic tire usually used in a passenger car.

Table 2

	Groove width (mm)	Groove depth (mm)	Groove angle *1 (°)
Circumferential main groove 21a, 21b	7	8	0
Steeply slant groove portion 5a, 5b	10	8	5 - 25
Gently slant groove portion 6a, 6b	4	6.5	70 - 80
Auxiliary groove 28	2	6.5	70 - 65
Curved part 29	6	8 - 6.5	25 - 70
Pseudo-land part 14a	Width of land: 8 - 0 mm, Length of land: 55 - 70 mm, Height of land: 8 - 0 mm		
Pseudo-land part 14b1	Width of land: 3 - 1 mm, Length of land: 30 - 25 mm, Height of land: 8 - 0 mm		
Pseudo-land part 14b2	Width of land: 6 - 4 mm, Length of land: 35 - 45 mm, Height of land: 8 - 0 mm		

*1: Angle with respect to the circumferential direction of tire

Conventional Example

[0041] A tire of this example is a pneumatic tire having a tread pattern shown in FIG. 5 and a tire size of PSR 205/55R16, in which dimensions of circumferential grooves 101-103, slant grooves 104-106 and the like are shown in Table 3.

Table 3

	Groove width (mm)	Groove angle (°)	Groove depth (mm)
Circumferential groove 101	8	0	8
Circumferential groove 102	7	0	8
Circumferential groove 103	3	0	8
Slant groove 104	4	80	6.5
Slant groove 105	4.5 - 5.0	50 - 70	6.5
Slant groove 106	5	75	6.5

Evaluation of tire performances

[0042] The drainage performance, steering stability and pattern noise are evaluated with respect to the above tires as follows.

[0043] Each of the above tires is mounted onto an approved rim (6×1/2 JJ) and subjected to the following tests under conditions that an internal pressure is 230 kPa and a load weight is the same as a weight when two crewman are ridden on the vehicle.

[0044] The drainage performance is evaluated during both the straight running and the cornering.

[0045] The drainage performance during the straight running is evaluated by straight running on a wet road surface having a water depth of 5 mm to measure a limit speed in the occurrence of hydroplaning phenomenon.

[0046] The drainage performance during the cornering is evaluated by running on a wet road surface having a water depth of 5 mm at a cornering radius of 80 m to measure a limit lateral G (gravity) in the occurrence of hydroplaning phenomenon.

[0047] The steering stability is evaluated by a feeling of a test driver when the vehicle is sport-run on a circuit course of a dry state at various running modes.

[0048] The pattern noise is evaluated by a feeling of a test driver on an indoor noise when the vehicle is run by inertia from 100 km/h on a straight and smooth road surface.

[0049] In Table 4 are shown these evaluation results, in which the numerical values in Table 4 are represented by an index on the basis that the conventional tire is 100. The larger the index value, the better the performance.

Table 4

5			Conventional Example	Example 1	Example 2
	Evaluation of performances	Drainage performance *1	100	110	115
		Drainage performance *2	100	105	110
		Steering stability *3	100	105	100
		Pattern noise	100	110	105

*1: During straight running

*2: During cornering

*3: During running on dry road surface

[0050] As is seen from the results of Table 4, Examples 1 and 2 are excellent in the drainage performance and steering stability as compared with those of the conventional example and reduce the pattern noise.

[0051] According to the invention, there can be provided pneumatic tires, particularly high-performance tires improving the drainage performance without sacrificing the other tire performances such as steering stability and the like.

Claims

1. A pneumatic tire comprising a tread portion (1) with a tread pattern defined by a plurality of slant grooves (7a,7b), each of said slant grooves comprising a steeply slant groove portion (5a,5b) located in a widthwise central region (2) of the tread portion, said steeply slant groove portion being inclined at a relatively small angle with respect to a circumferential direction (4) of the tire, and one end (9) of the steeply slant groove portion which is close to an equatorial plane of the tire extending toward the other end (8) of the steeply slant groove portion which is close to a tread end, and a gently slant groove portion (6a,6b) located in a side region (3a,3b) of the tread portion, said gently slant groove portion being inclined at a relatively large angle with respect to the circumferential direction of the tire, and said gently slant groove portion extending from the end (8) of the steeply slant groove portion or an extension thereof so as to open at the tread end (19a,19b), **characterized in that** an opening groove width (W1) located at said other end (8) of the steeply slant groove portion (5a,5b) is wider than an opening groove width (W2) located at said one end (9) of the steeply slant groove portion, and the steeply slant groove portion extending in a longitudinal direction of the slant groove (7a,7b) comprises a groove edge part (31) forming a boundary to an outer surface (33) of a tread land portion, a main groove bottom part (32) mainly forming a groove bottom of the steeply slant groove portion, and a pseudo-land part (14) located in the groove edge part (31) and adjacent to at least one of both side edges (32a,32b) of the main groove bottom part (32), and the pseudo-land part (14) has such a slant surface (13) that a height thereof is gradually decreased from the groove edge part (31) toward the main groove bottom part (32).
2. A pneumatic tire as claimed in claim 1, **characterized in that** the steeply slant groove portion (5a,5b) of the slant groove (7a,7b) extends at an angle of not more than 30° with respect to the circumferential direction (4) of the tire.
3. A pneumatic tire as claimed in claim 1 or 2, **characterized in that** the slant surface (13) of the pseudo-land part (14) has substantially a triangular shape or a trapezoidal shape when viewing the tire from the front thereof.
4. A pneumatic tire as claimed in any of claims 1 to 3, **characterized in that** a pair of adjoining slant grooves (7a, 7b) located on both sides of a pattern center (10) are formed at a phase difference (L) of a half pitch in the circumferential direction (4) of the tire.
5. A pneumatic tire as claimed in any of claims 1 to 4, **characterized in that** one circumferential main groove (21a, 21b) extending along the circumferential direction (4) of the tire is arranged at a widthwise center position of each tread half region (20a,20b) defined between the pattern center (10) and the tread end (19a,19b) or arranged in the vicinity of the widthwise center position of the tread half region.
6. A pneumatic tire as claimed in any of claims 1 to 5, **characterized in that** the gently slant groove portion (6a,6b) of the slant groove (7a,7b) extends at an angle of 70-85° with respect to the circumferential direction (4) of the tire.

EP 1 197 355 A2

7. A pneumatic tire as claimed in any of claims 1 to 6, **characterized in that** at least one rib-shaped land (22) and at least two land rows (23a,23b,24a,24b) each comprised of plural blocks, which extend along the circumferential direction (4) of the tire, are formed on the tread portion.
- 5 8. A pneumatic tire as claimed in any of claims 1 to 7, **characterized in that** the pseudo-land part (14) is arranged adjacent to a side edge (32a,32b) of the main groove bottom part (32) located at the pattern-center-side of the main groove bottom part in the steeply slant groove portion (5a,5b).
- 10 9. A pneumatic tire as claimed in any of claims 1 to 7, **characterized in that** pseudo-land parts (14a,14b) are arranged adjacent to both side edges (32a,32b) of the main groove bottom part (32) in the steeply slant groove portion (5a,5b).

15

20

25

30

35

40

45

50

55

FIG. 1




FIG. 2A FIG. 2B FIG. 2C




FIG. 3






FIG. 4A




I - I Section

FIG. 4B




II - II Section

FIG. 4C




III - III Section

FIG. 4D



IV - IV Section

FIG. 5
PRIOR ART



THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)